





	NAME/MANUFACTURER/COMPUTER	LOCATION	COUNTRY	CORES	R _{max} P _{1000/s}
1	K Computer SPARC64 VIIIfx 2.0GHz, Tofu interconnect	RIKEN	Japan	548,352	8.16
2	Tianhe-1A 6-core Intel X5670 2.93 GHz + Nvidia M2050 GPU w/custom interconnect	NUDT/NSCC/Tianjin	China	186,368	2.56
3	Jaguar Cray XT-5 6-core AMD 2.6 GHz w/custom interconnect	DOE/SC/ORNL	USA	224,162	1.76
4	Nebulae Dawning TC3600 Blade Intel X5650 2.67 GHz, NVidia Tesla C2050 GPU w/ lband	NSCS	China	120,640	1.27
5	Tsubame 2.0 HP Proliant SL390s G7 nodes (Xeon X5670 2.93GHz), NVIDIA Tesla M2050 GPU w/lband	TiTech	Japan	73,278	1.19



HPLINPACK

A Portable Implementation of the High Performance Linpack Benchmark for Distributed Memory Computers

- Algorithm: recursive panel factorizations, multiple lookahead depths, bandwidth reducing swapping
- Easy to install, only needs MPI + BLAS or VSIPL
- Highly scalable and efficient from the smallest cluster to the largest supercomputers in the world

FIND OUT MORE AT <http://icl.eecs.utk.edu/hpl/>